US009965995B2

(12) **United States Patent**
Chen et al.

(10) **Patent No.: US 9,965,995 B2**
(45) **Date of Patent: May 8, 2018**

(54) **ELECTRONIC DEVICE HAVING DISPLAY WITH CURVED EDGES**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(72) Inventors: **Yu Cheng Chen**, San Jose, CA (US); **Tsung-Ting Tsai**, Taipei (TW); **Shih Chang Chang**, Cupertino, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 85 days.

(21) Appl. No.: **14/990,606**

(22) Filed: **Jan. 7, 2016**

(65) **Prior Publication Data**

US 2016/0351107 A1 Dec. 1, 2016

Related U.S. Application Data

(60) Provisional application No. 62/169,453, filed on Jun. 1, 2015.

(51) **Int. Cl.**

G09G 3/20	(2006.01)
G02F 1/1345	(2006.01)
G09G 3/36	(2006.01)

(52) **U.S. Cl.**

CPC ***G09G 3/2092*** (2013.01); ***G02F 1/1345*** (2013.01); ***G09G 3/20*** (2013.01); ***G09G 3/3666*** (2013.01); *G02F 2201/56* (2013.01); *G09G 2300/0426* (2013.01); *G09G 2300/0439* (2013.01); *G09G 2300/08* (2013.01); *G09G 2310/0221* (2013.01); *G09G 2310/0264* (2013.01); *G09G 2310/0281* (2013.01); *G09G 2310/0286* (2013.01)

(58) **Field of Classification Search**

USPC 349/143, 149, 150, 158

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,052,101	A *	4/2000	Moon	G09G 3/2022 345/60
8,310,614	B2 *	11/2012	Sasaki	G02F 1/1333 349/158
8,599,351	B2	12/2013	Kim	

(Continued)

FOREIGN PATENT DOCUMENTS

CN	1952764	7/2010
KR	20080044434	5/2008

(Continued)

Primary Examiner — Jennifer Mehmood
Assistant Examiner — Deeprose Subedi
(74) *Attorney, Agent, or Firm* — Treyz Law Group, P.C.; G. Victor Treyz; Joseph F. Guihan

(57) **ABSTRACT**

A display may have an array of pixels. The array of pixels may have a shape such as a circular shape or other shape with a curved edge. Display driver circuitry may supply data signals to the pixels using folded vertical data lines and bisected horizontal gate lines. Each folded vertical lines may have a first segment in a left half of the array and a second segment in a right half of the display. Curved coupling segments in an inactive area of the display may be used in joining the first and second segments. Display driver circuits may be provided in top and bottom portions of the inactive area to supply data to respective top and bottom portions of the array. Gate driver output buffers may have different strengths in different rows of the array.

17 Claims, 9 Drawing Sheets